







RoHS Compliance



Recommended P.C.B Layout
Total tolerance $\pm 0.05\text{mm}$




Circuit	Dimensions(mm)			
	A	B	C	D
02	0.80	1.90	3.78	3.04
03	1.60	2.70	4.58	3.84
04	2.40	3.50	5.38	4.64
05	3.20	4.30	6.18	5.44
06	4.00	5.10	6.98	6.24
07	4.80	5.90	7.78	7.04
08	5.60	6.70	8.58	7.84
09	6.40	7.50	9.38	8.64
10	7.20	8.30	10.18	9.44
11	8.00	9.10	10.98	10.24
12	8.80	9.90	11.78	11.04
13	9.60	10.70	12.58	11.84
14	10.40	11.50	13.38	12.64
15	11.20	12.30	14.18	13.44
16	12.00	13.10	14.98	14.24
17	12.80	13.90	15.78	15.04
18	13.60	14.70	16.58	15.84
19	14.40	15.50	17.38	16.64
20	15.20	16.30	18.18	17.44



Material:
Housing: Nylon or LCP, UL 94V-0
Terminal: Phosphor Bronze
Finish: Plated Tin or Gold Flash
Lead over Nickel

Electrical Characteristics:
Current rating: 0.5A AC, DC
Voltage rating: 30V AC, DC
Temperature range: $-35^{\circ}\text{C} \sim +85^{\circ}\text{C}$
Insulation resistance: $100\text{M}\Omega/\text{Min.}$
Withstanding voltage: 200V AC/minute
Contact resistance: $20\text{m}\Omega/\text{Max.}$

Order Information:
L-KLS1-XL1-0.80-XX-VM
L: RoHS
0.80mm Pitch
XX-No. of 2~20pin
Type: H-Hosing T-Terminal
VM-Vertical SMT Pin
RM-Horizontal SMT Pin



ANGLE TOLERANCE	PROJECTION	Description:		
$\pm 3^{\circ}$			0.80mm Pitch SUR	
			Wire to board connector	
GENERAL TOLERANCE	UNITS	mm	KLS P/N:	L-KLS1-XL1-0.80-XX-VM
x.x ± 0.30	SHEET SIZE	A4		
x.xx ± 0.20	Draw:	Daniel	2020-11-11	
x.xxx ± 0.10	Check:	Daniel	2020-11-11	



NingBo KLS ELECTRONIC CO.,LTD.