




Material:
Housing:PA66 ,UL 94 V-0,
Colour:Natural

Electrical Characteristics:
Current rating:1.0A AC,DC
Voltage rating:50V AC,DC
Temperature range:-25℃ ~ + 85℃
Insulationresistance:100MΩ/Min.
Withstanding voltage:500V AC/minute
Contact resistance:20mΩ/Max.



Pins	Dimensions(mm)		
	A	B	C
02	1.00	3.00	2.40
03	2.00	4.00	3.40
04	3.00	5.00	4.40
05	4.00	6.00	5.40
06	5.00	7.00	6.40
07	6.00	8.00	7.40
08	7.00	9.00	8.40
09	8.00	10.00	9.40
10	9.00	11.00	10.40
11	10.00	12.00	11.40
12	11.00	13.00	12.40
13	12.00	14.00	13.40
14	13.00	15.00	14.40
15	14.00	16.00	15.40
16	15.00	17.00	16.40
17	16.00	18.00	17.40
18	17.00	19.00	18.40
19	18.00	20.00	19.40
20	19.00	21.00	20.40

Order Information:
L-KLS1-XF4-1.00-XX-H2

L: RoHS
1.00mm Pitch
XX-No.of 02 ~20pin
Type:H-Hosing
H2-Hosing T-Terminal
VM-Vertical SMT Pin RM-Horizontal SMT Pin

ANGLE TOLERANCE		PROJECTION		Description:	
±3°				1.00mm Pitch wire to board connector	
GENERAL TOLERANCE		UNITS	mm	KLS P/N:	L-KLS1-XF4-1.00-XX-H2
x.x	±0.30	SHEET SIZE	A4	NingBo KLS ELECTRONIC CO.,L TD.	
x.xx	±0.20	Draw:	Daniel		
x.xxx	±0.10	Check:	Daniel		
				2020-11-11	
				2020-11-11	