	<b>KLS23-B3630M</b>	Output Power: 1W~16W	Weight: 110g (Approx.)
	<b>Brushless DC Motor-Typical Application</b> Home Application: White Goods, Small Appliance, Fanner, Electric Curtain Medical Apparatus: Medical Pump, Surgery Tools, Medical Stirrer, centrifugal Machine Industry Equipment: Electric Valve, Actuator, Small Pump Business Equipment: Printer, Copier, Projector, ATM, Vending Machine Personal Care: Hair Dryer, Electric Shaver, Massager		


Model	Voltage(V)		No Load		Rated Load				Starting	
	Operating Range	Rated	Speed (rpm)	Current (A)	Torque (mNm)	Speed (rpm)	Current (A)	Output P. (W)	Torque (mNm)	Current (A)
B3630M-S01	5-12	6	2940	0.39	10.00	2270	0.91	2.38	44.05	2.68
B3630M-S02	8-26	12	5200	0.27	14.72	4260	0.90	6.56	81.30	3.75
B3630M-S03	8-26	24	6970	0.20	19.62	5640	0.76	11.58	102.51	3.13

**Characteristic:** CW & CCW, Signal function available, Locked rotor protection, Stepless speed regulation, Low noise, Low EMI, Long life 10000-50000hrs

**Notice:** Data in this typical specification sheet are for other certain customer. Voltage, rated torque, speed, current, power and shaft extension feature & dimension can be changed to meet customer specific requirement.

**Outline Drawing:** Usable machine screw length 3.0mm max from motor mounting surface

Unit: Millimeter



### Performance Curve

B3630M-S02

12V

B3630M-S03

24V

