

UK Rail-Mounted Terminal Block



UK2.5B



| | | |
|--|----------------|------------------------|
| Standard | UL | IEC |
| Voltage | 600V | 800V |
| Current | 20A | 24A |
| Wire Size | 24-12AWG | 0.2-2.5mm ² |
| T/W/End plate | 6.2/42.5/1.5mm | |
| Height(NS35 : 7.5 / NS35 : 15 / NS32) | 42/49.5/47mm | |
| Rated Surge Voltage/Contamination Class | 8kV/3 | |
| Stripping Length | 7 mm | |
| Screw Thread/Tightening Torque | M3/0.5Nm | |
| Internal Cylindrical Gage | A3 | |
| Insulating Material/Inflammability Class | PA/V-0 | |
| | | |
| Specification | Model | |
| (1)Terminal Block | UK 2.5B | |
| (2)End Cover | D-UK2.5 | |
| (3)Fixed Bridge | 2-P | FBI 2-6 |
| | 3-P | FBI 3-6 |
| | 5-P | FBI 5-6 |
| | 10-P | FBI 10-6 |
| (4)Step Bracket | | |
| (5)Insertion Bridge | 2-P | EB 2-6 |
| | 3-P | EB 3-6 |
| | 10-P | EB 10-6 |
| (6)Isolator Bridge Bar, 10 P | ISSBI 10-6 | |
| (7)Bridge Bar Isolator | IS-K4 | |
| (8)Sw itching Bridge | USBR 2-7 | |
| (9)Separating Plate | TS-KK3 | |
| (10)Separating Plate, Width:1.5mm | ATP-PC | |
| (11)Test Plug Socket | PSB 3/10/4 | |
| (12)Test Plug Socket, Insulated | PSBJ 3/13/4 | |
| (13)Zack Strip | ZB 6 | |