



PCB LAYOUT

Material
 Screw: M4.0, steel, Zn plated
 Cage: Brass, Nickel plated
 Pin header: Brass, Tin plated
 Housing: PA66, UL94V-0, Green

Electrical
 Rated voltage: 300V
 Rated current: 60A
 Wire range: 20~6AWG 10mm²
 Contact Resistance: 20 mΩ
 Insulation resistance: 500MΩ/DC1000V
 Withstand voltage: AC2500V / 1min

Mechanical
 Temp. Range: -40 °C ~ +105 °C
 Soldering: 250 °C 5Sec. Max.
 Torque: 1.2 Nm (10.5 Lb.) in
 Strip length: 9~10 mm

Order Information

L-KLS2-116-10.16-XXP-4 S XX
 RoHS Terminal Block
 Pitch
 No. of Pole
 Color: 4- Green
 Screw: S- Slot Screw
 Code: Product Code: 00~99

GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION		Description:	
X: ±0.60	X: ±5°	UNITS	mm	Screw CONN TERM BLOCK 10.16MM			
.X ±0.38	.X ±3°	SHEET SIZE	A4	KLS2-116-10.16-XXP-4C			
.XX ±0.25	.XX ±2°	KLS P/N:					
Draw by: Date	2015-09-01						
Check by: Date	2015-09-15						
SCALE	SHEET	OF					

KLS ELECTRONIC CO., LTD.