



Material
Housing: PA66, UL94V-0
Clamp: Steel Zinc plated
Pin Header: Brass, Tin plated
Screw: M2.5, steel Zinc plated

Electrical
Rated voltage: 300V
Rated current: 20A
Contact Resistance: 20 mΩ
Insulation resistance: 500MΩ/DC500V
Withstand voltage: AC2000V / 1 min
Wire Range: 24 ~ 14AWG 2.5mm²

Mechanical
Temp. Range: -40 °C ~ +105 °C
Strip length: 12 ~ 13mm
Torque: 0.4Nm (3.5Lb.in)

Order Information

L-KLS2-146R-5.00-XXP-4S00

RoHS
Terminal Block
Pitch
No.: of Pole
Color: 4- Green
Screw: S-Slot Screw
Product Code: 00 ~ 99

GENERAL TOLERANCE		ANGLE TOLERANCE		Description:	
X. ±0.60	.X ±0.38	X. ±5°	.X ±3°	Screw CONN TERM Block 5.00mm	
.XX ±0.25		.XX ±2°		KLS P/N:	KLS2-146R-5.00-XXP-4S
Draw by	2015-09-01	PROJECTION			NingBo KLS ELECTRONIC CO.,L TD.
Check by	2015-09-15	UNITS	mm		
SCALE		SHEET SIZE	A4		