

Material
Housing: PA66, UL 94 V-0
Shrapnel: Stainless steel
Clamp: Phosphor bronze, Tin plated



Electrical
Rated voltage: 300 V
Rated current: 8 A
Contact Resistance: 20 mΩ
Withstand voltage: AC 2000V / 1 Min
Insulation resistance: 500 MΩ / DC 500V
Wire Range: 24 ~ 16 AWG 1.0 mm²

Mechanical
Temp. Range: -40 °C ~ +105 °C
Strip length: 9-10 mm

Order Information

L-KLS2-FMCC-3.50-XXP-4 00

RoHS —
Terminal Block —
Pitch —
No. of Pole —
Color: 4- Green —
Product Code: 00 ~ 99 —

GENERAL TOLERANCE		ANGLE TOLERANCE		Description:	
X. ±0.60		X. ±5°		Pluggable Terminal Block 3.5 MM	
.X ±0.38		.X ±3°		KLS P/N:	KLS2-FMCC-3.50-XXP-4-00
.XX ±0.25		.XX ±2°		 NingBo KLS ELECTRONIC CO.,L TD.	
Draw by	2015-09-01	PROJECTION			
Check by	2015-09-15	UNITS	mm		
SCALE		SHEET SIZE	A4		