



Material
 Housing: PA66, UL 94 V-0
 Shrapnel: Stainless steel
 Clamp: Phosphor bronze, Tin plated

Electrical
 Rated voltage: 300 V
 Rated current: 8 A
 Contact Resistance: 20 mΩ
 Withstand voltage: AC 2000V / 1 Min
 Insulation resistance: 500 MΩ / DC 500V
 Wire Range: 24 ~ 16 AWG 1.0 mm²

Mechanical
 Temp. Range: -40 °C ~ +105 °C
 Strip length: 9-10 mm

Order Information

L-KLS2-FMDD-3.50-XXP-4 00

- RoHS
- Terminal Block
- Pitch
- No. of Pole
- Color: 4- Green
- Product Code: 00 ~ 99

GENERAL TOLERANCE		ANGLE TOLERANCE		Description:	
X. ±0.60	.X ±0.38	.XX ±0.25	X. ±5°	.X ±3°	.XX ±2°
Draw by 2015-09-01			PROJECTION		
Check by 2015-09-15			UNITS mm		
SCALE			SHEET SIZE A4		
				NingBo KLS ELECTRONIC CO.,L TD.	
				Pluggable Terminal Block 3.5 MM KLS P/N: KLS2-FMDD-3.50-XXP-4-00	