



1	2		3		4		5		6		7		8	
RoHS Compliance	P/N		Nominal DC Spark-over voltage		Deviation of VS		Impulse spark-over voltage		Impulse discharge current		Insulation resistance		Transverse voltage duration	
With Radial Lead and expiration protects	With Radial Lead		100V/s		100V/μs		1KV/μs		10/350μs 1cycles		50Hz 10cycles		1MHz	
			V		V		V		KA		Ω		pF	
L-KLS5-GDTM7512-3R090LF	L-KLS5-GDTM7512-3R090L		90		±20%		≤500		4.0		≥10 ⁸		≤200	
L-KLS5-GDTM7512-3R150LF	L-KLS5-GDTM7512-3R150L		150		±20%		≤550		4.0		≥10 ⁹		≤200	
L-KLS5-GDTM7512-3R230LF	L-KLS5-GDTM7512-3R230L		230		±20%		≤600		3.0		≥10 ⁹		≤200	
L-KLS5-GDTM7512-3R250LF	L-KLS5-GDTM7512-3R250L		250		±20%		≤650		3.0		≥10 ⁹		≤200	
L-KLS5-GDTM7512-3R350LF	L-KLS5-GDTM7512-3R350L		350		±20%		≤800		2.0		≥10 ⁹		≤200	
L-KLS5-GDTM7512-3R470LF	L-KLS5-GDTM7512-3R470L		470		±20%		≤1000		2.0		≥10 ⁹		≤200	
L-KLS5-GDTM7512-3R600LF	L-KLS5-GDTM7512-3R600L		600		±20%		≤1200		2.0		≥10 ⁹		≤200	

With Radial Lead

With Radial Lead and expiration protects



PROJECTION		Description:	
		7.5x12.0mm 3 POLE THROUGH HOLE GAS DISCHARGE TUBE	
UNITS	mm	KLS P/N:	L-KLS5-GDTM7512-XXXX
SHEET SIZE	A4		
Draw:	Daniel	2020-06-29	NingBo KLS ELECTRONIC CO.,LTD.
Check:	Daniel	2020-06-29	