



7		8
Part Number		Current Rating
L-KLS5-275A-080-A		80A
L-KLS5-275A-100-A		100A
L-KLS5-275A-125-A		125A
L-KLS5-275A-150-A		150A
L-KLS5-275A-180-A		180A
L-KLS5-275A-200-A		200A
L-KLS5-275A-250-A		250A
L-KLS5-275A-500-A		500A

Characteristics:
 Voltage Rating: 32V DC
 Current Rating: 80A ~ 500A
 Operating Temperature: -40°C to +125°C

Material:
 Body: PA66,Black
 Contact: Copper Alloy

Time-Current Characteristics

% of Rating	Opening Time	
	80 ~ 250	300 ~ 500
75	-----	1440s Min.
100	1440s Min.	-----
135	120s to 1800s	-----
200	1s to 15s	1s
350	0.3s to 5s	0.3s to 5s
600	0.1s to 1s	-----

4	Connector	Brass Alloy	4
3	Cover	PA66,Black	1
2	Base	PA66,Black	1
1	Contact	Copper Alloy	1
ITEM	Description	Material	Q'ty

GENERAL TOLERANCE	PROJECTION		Description:
X. ±0.5	UNITS	mm	32V Mega Bolt-Down Fuse
.X ±0.25	SCALE	1:1	
.XX ±0.15	Draw by:	Daniel	
ANGLE TOLERANCE	Check by:	Daniel	KLS P/N: L-KLS5-275A-XXX-A
X. ±5°	Date	2022-09-01	NingBo KLS ELECTRONIC CO.,L TD.
.X ±3°	SHEET	1 OF 1	
.XX ±2°			