



Characteristics:
 Voltage Rating: 32V
 Current Rating: 30A Max.
 Insulation Resistance: 100MΩ Min. at 500VDC
 Dielectric Strength : AC 1000 V Min.at 60s

Fuse type:
 Medium Blade Fuse: KLS5-269-xxx

Order Information:
 L - KLS5 - 707E -XX R xxx
 L: RoHS
 Wire AWG:
 12- 12AWG for 30A Max.
 14- 14AWG for 20A Max.
 16- 16AWG for 15A Max.
 18- 18AWG for 10A Max.
 20- 20AWG for 5A Max.
 Cable Color: R- Red
 Cable Long: 300-300mm

| | | | |
|------|----------|--|------|
| 4 | Cable | UL1015 PVC Cable 12~16AWG Red,L=300mm | 1 |
| 3 | Seal | Silicone rubber ,Orange | 2 |
| 2 | Terminal | Female Terminal,Brass T=0.4mm,Tin Plated | 2 |
| 1 | Housing | Housing For Fuse,PC&PBT,Black | 1 |
| Item | P/N | Describe&Material | Q'ty |

| | | | |
|-------------------|------------|------------|--|
| GENERAL TOLERANCE | PROJECTION | | Description: |
| .X ±1.00 | UNITS | mm | Miniature Blade Fuse Holder With Cable |
| .X ±0.50 | Draw by: | Daniel | |
| .XX ±0.30 | Check by: | Daniel | |
| ANGLE TOLERANCE | Date | 2022-09-01 | NingBo KLS ELECTRONIC CO.,L TD. |
| ±5° | SHEET | 1 OF 1 | |