



Characteristics:
 Voltage Rating: 32V
 Current Rating: 30A Max.
 Insulation Resistance: 100MΩ Min. at 500VDC
 Dielectric Strength : AC 1000 V Min.at 60s

Fuse type:
 Medium Blade Fuse: KLS5-269-xxx

Order Information:

L - KLS5 - 707F -XX R xxx

L: RoHS

Wire AWG:

- 12- 12AWG for 30A Max.
- 14- 14AWG for 20A Max.
- 16- 16AWG for 15A Max.
- 18- 18AWG for 10A Max.
- 20- 20AWG for 5A Max.

Cable Color: R- Red

Cable Long: 300-300mm

3	Cable	UL1015 PVC Cable 12~20AWG Red,L=300mm	1
2	Terminal	Female Terminal,Brass T=0.3mm,Tin Plated	2
1	Housing	Housing For Fuse,PVC,Black	1
Item	P/N	Describe&Material	Q'ty

GENERAL TOLERANCE	PROJECTION		Description:
.X ±1.00	UNITS	mm	Miniature Blade Fuse Holder With Cable
.X ±0.50	Draw by:	Daniel	KLS P/N: L-KLS5-707F-xxR300
.XX ±0.30	Check by:	Daniel	NingBo KLS ELECTRONIC CO.,L TD.
ANGLE TOLERANCE	Date	2022-09-01	
±5°	SHEET	1 OF 1	