## NINGBO KLS ELECTRONIC CO; LTD

Ø11.8

Π


49.7 42.5 \_\_\_\_\_\_24.2

## **LT500 SERIES PHOTOCONTROL LAMPHOLDER**




LT510





LT520





LT530



LT540

LT560





## FEATURE

- > Compatible with Incandescent & CFL & LED bulbs
- Self-Tightening Dusk to Dawn Light Control
- > No wiring required simply screw-in
- > Turns light On at dusk, Off at dawn
- > Compact design fits smaller enclosed outdoor fixtures
- > Weather resistant and reliable solid state circuitry

TECHNICAL SPECIFICATION	
Standard	UL496
Rated Volts	120V/240V
Rated Load	150W Max*
Frequency	50/60 Hz
Fail Mode	ON
Turn-On Light Levels	10-16 Lux
Turn-Off Light Levels	<65 Lux
Action Time	3-15 sec
Operating Temperature	-40°℃ to +70°℃
<b>Related Humidity</b>	96%
Switch	> 5000 ON/OFF Operations at Rated Load
Power Consumption	≤ 0.7 watts at 120VAC
Lamp Cap	E26/E27**
Lamp Holder	E26/E27**
* LT510: 100W max ** LT510: E12	

## WWW.KLSELE.COM