



1
RoHS Compliance

6	7	8
REV	SYM	Revision Record
V0	KLS08052	New Version Release
		Appr.
		WuHao
		Date
		2024-12-18



Item No.	Dimension						Material	Color
	A	B	C	D	E			
LKLS8-0222-PTO-220	$\phi 6.0 \pm 0.1$	$\phi 3.55 \pm 0.05$	$\phi 3.0 \pm 0.05$	1.5 ± 0.1	1.2 ± 0.1	PA66	Natural	
L-KLS8-0222-PTO-220A	$\phi 6.0 \pm 0.1$	$\phi 3.55 \pm 0.05$	$\phi 3.0 \pm 0.05$	2.0 ± 0.1	1.2 ± 0.1	PA66	Natural	
L-KLS8-0222-PTO-220B	$\phi 6.0 \pm 0.1$	$\phi 3.55 \pm 0.05$	$\phi 3.0 \pm 0.05$	2.5 ± 0.1	1.5 ± 0.1	PA66	Natural	
L-KLS8-0222-PTO-220D	$\phi 6.0 \pm 0.1$	$\phi 3.55 \pm 0.05$	$\phi 3.0 \pm 0.05$	3.0 ± 0.1	1.5 ± 0.1	PA66	Natural	
L-KLS8-0222-PTO-3	$\phi 8.0 \pm 0.1$	$\phi 3.8 \pm 0.05$	$\phi 3.0 \pm 0.05$	3.0 ± 0.1	2.0 ± 0.1	PA66	Natural	
L-KLS8-0222-CTW-8N	$\phi 8.0 \pm 0.1$	$\phi 3.8 \pm 0.05$	$\phi 3.1 \pm 0.05$	1.2 ± 0.1	1.2 ± 0.1	PA66	Natural	
L-KLS8-0222-CTW-9N	$\phi 10.0 \pm 0.1$	$\phi 6.0 \pm 0.05$	$\phi 5.0 \pm 0.05$	5.0 ± 0.1	1.0 ± 0.1	PA66	Natural	
L-KLS8-0222-CTW-5PS	$\phi 5.46 \pm 0.2$	$\phi 3.43 \pm 0.2$	$\phi 2.95 \pm 0.2$	0.8 ± 0.2	1.02 ± 0.2	PPS+GF UL 94 V-0	Black	
---	---	---	---	---	---	---	---	

Notes:
 Temperature resistance: $-20^{\circ}\text{C} \sim +110^{\circ}\text{C}$
 Shrinking Is Normal Status
 Usage: Used for fixing PC boards and substrates, insulation, rust free, lightweight

ANGLE TOLERANCE	PROJECTION	Description:
$\pm 3^{\circ}$		Transistor Bushing
GENERAL TOLERANCE	UNITS	mm
x.x ± 0.30	SHEET SIZE	A4
x.xx ± 0.20	Draw:	WuHao 2024-12-18
x.xxx ± 0.10	Check:	Daniel 2024-12-18
		KLS P/N: L-KLS8-0222-CTW-5PS

