

1

2

3

4

5

6

7

8

RoHS Compliance

REV

SYM

Revision Record

Appr.

Date

V0

KLS15012

New Version Release

Song

2025-03-18

Pin Number

Series	02	03	04	05	06	07	08	10	12	14	16	18	19	26	32
Pin Number															
Pin size	2.0mm	1.6mm	1.3mm	1.3mm	1.3mm	1.3mm	0.9mm	0.9mm	0.7mm	0.7mm	0.7mm	0.7mm	0.7mm	0.5mm	0.5mm
Conductor size	14AWG	16AWG	20AWG	20AWG	20AWG	20AWG	22AWG	22AWG	22AWG	22AWG	22AWG	22AWG	22AWG	28AWG	28AWG
Rated current	25A	17A	15A	14A	12A	11A	10A	8A	7A	6.5A	6.0A	5.5A	5.0A	2.0A	1.5A

Material:

1.Outer shell:Brass,Chrome plated

2.Locking washer: SUS 301

3.Hexagon nut: Brass, Nickel plated

4.Grounding crown: Brass, Nickel plated

5.Insulator: PPS

6.Pin: Phosphor Copper, Gold Plated

Technical Characteristics:

Environment:Indoor

Ingress protection:IP50

Rated Temperature:-25°~+150°

Durability:500 Cycles Min

Salt Spray Test: 144h Min

Order Information

L-KLS15-B-ZGG.2B.3 08

RoHS

XXX-No.of 02~32 Pin

ANGLE TOLERANCE	PROJECTION	Description:			
±3°			Metal Circular Connector		
GENERAL TOLERANCE	UNITS	mm	KLS P/N:	L-KLS15-B-ZGG.2B.3XX	
.x ±0.30	SHEET SIZE	A4			
.xx ±0.20	Draw:	Song	2025-03-18		NingBo KLS ELECTRONIC CO.,L TD.
.xxx ±0.10	Check:	Daniel	2025-03-18		

1

2

3

4

5

6

7

8