




RoHS Compliance

REV	SYM	Revision Record	Appr.	Date
V0	KLS01695	New Version Release	Jenny	2025-05-07

Material:
Housing:Polycarbonate,UL94V-0
Colour:RAL 7032 (Light grey)
Contacts:Copper Alloy,Hard-silver plated
Hard-gold plated
Wire gauge:1.0-2.5mm² (18-14 AWG)
Terminal:Crimp Terminal

Electrical Characteristics:
Number of contacts:32+PE
Rated Current:16A
Rated Voltage-ground:250V
Rated Impulse Voltage:4KV
Pollution Degree:3
Rated Voltage Acc.to UL CSA:600V
Insulation Resistance:10¹⁰Ω Min
Contact Resistance:1mΩ Max
Limiting Temperatures:-40℃~+125℃
Mating cycles:500 Times Min

Order Information:
L-KLS1-HA-032 FC
L:RoHS
HA series
No of contacts
Type:
Female Crimp Terminal

ANGLE TOLERANCE	PROJECTION	Description:	Heavy Duty Connectors,HA series 32 Contacts,Female Crimp Terminal
±3°			
GENERAL TOLERANCE	UNITS	mm	KLS P/N:
x.x ±0.30	SHEET SIZE	A4	L-KLS1-HA-032FC
x.xx ±0.20	Draw:	Jenny	2025-05-07
x.xxx ±0.10	Check:	Daniel	2025-05-07



NingBo KLS ELECTRONIC CO.,L TD.