

1		2		3		4		5		6		7		8	
RoHS Compliance															
REV		SYM		Revision Record				Appr.		Date					
V0		KLS08269		New Version Release				Song		2025-10-15					
V1		△		Process Improvement				Song		2026-09-29					

Item	Mounting Holes	PANEL THICKNESS	A	B	C	D	E
L-KLS8-0217-CSR2-2.4X	2.1	0.6-1.2	4.2	1.2	2.4	2.0	3.5
L-KLS8-0217-CSR2-3.2X		1.3-2.0			3.2		
L-KLS8-0217-CSR2-4X		2.1-2.8			4.0		
L-KLS8-0217-CSR2-4.8X		2.9-3.6			4.8		
L-KLS8-0217-CSR2-5.6X		3.7-4.4			5.6		
L-KLS8-0217-CSR2-6.4X		4.5-5.2			6.4		
Item	Mounting Holes	PANEL THICKNESS	A	B	C	D	E
L-KLS8-0217-CSR2.7-3.2X	2.7	1.0-2.0	5.0	1.4	3.2	2.6	4.8
L-KLS8-0217-CSR2.7-4.2X		2.1-3.0			4.2		
L-KLS8-0217-CSR2.7-4.8X		2.7-3.6			4.8		
L-KLS8-0217-CSR2.7-5.5X		3.4-4.6			5.5		
L-KLS8-0217-CSR2.7-6.5X		4.4-5.5			6.5		
L-KLS8-0217-CSR2.7-7.2X		5.1-6.0			7.2		
Item	Mounting Holes	PANEL THICKNESS	A	B	C	D	E
L-KLS8-0217-CSR3-3.5X	3.1	1.0-2.0	6.4	1.6	3.5	3.0	9.0
L-KLS8-0217-CSR3-4.5X		3.0-3.0			4.5		
L-KLS8-0217-CSR3-5.5X		3.0-4.0			5.5		
L-KLS8-0217-CSR3-6.5X		4.0-5.0			6.5		
L-KLS8-0217-CSR3-7.5X		5.0-6.0			7.5		
L-KLS8-0217-CSR3-8X		5.5-6.5			8.0		
L-KLS8-0217-CSR3-9X		6.5-7.5			9.0		
L-KLS8-0217-CSR3-10X		7.5-8.5			10.0		
L-KLS8-0217-CSR3-23X		20.5-21.5			23.0		
Item	Mounting Holes	PANEL THICKNESS	A	B	C	D	E
L-KLS8-0217-CSR3.5-3.5X	3.5	1.2-2.1	6.4	1.6	3.5	3.5	5.1
L-KLS8-0217-CSR3.5-4.5X		2.2-3.1			4.5		
L-KLS8-0217-CSR3.5-5X		2.7-3.6			5.0		
L-KLS8-0217-CSR3.5-5.5X		3.2-4.1			5.5		
L-KLS8-0217-CSR3.5-6X		3.7-4.6			6.0		
L-KLS8-0217-CSR3.5-7X		4.7-5.5			7.0		
L-KLS8-0217-CSR3.5-8X		5.7-6.5			8.0		
Item	Mounting Holes	PANEL THICKNESS	A	B	C	D	E
L-KLS8-0217-CSR4-5X	4.1	2.5-3.5	8.0	1.8	5.0	4.0	7.1
L-KLS8-0217-CSR4-6X		3.5-4.5			6.0		
L-KLS8-0217-CSR4-7X		4.6-5.5			7.0		
L-KLS8-0217-CSR4-8X		5.5-6.5			8.0		
L-KLS8-0217-CSR4-9X		6.5-7.5			9.0		
L-KLS8-0217-CSR4-10X		7.5-8.5			10.0		
L-KLS8-0217-CSR4-12X		9.0-10.5			12.0		
Item	Mounting Holes	PANEL THICKNESS	A	B	C	D	E
L-KLS8-0217-CSR5-4.5X	5.1	1.5-2.5	9.0	2.2	4.5	5.0	8.5
L-KLS8-0217-CSR5-5.5X		2.5-3.5			5.5		
L-KLS8-0217-CSR5-6.5X		3.5-4.5			6.5		
L-KLS8-0217-CSR5-7.5X		4.5-5.5			7.5		
L-KLS8-0217-CSR5-8.5X		5.5-6.5			8.5		
L-KLS8-0217-CSR5-9.5X		6.5-7.5			9.5		
L-KLS8-0217-CSR5-10.5X		7.5-8.5			10.5		
Item	Mounting Holes	PANEL THICKNESS	A	B	C	D	E
L-KLS8-0217-CSR6-6X	6.1	2.5-4.0	12.0	2.5	6.0	6.0	9.0
L-KLS8-0217-CSR6-8X		4.0-5.5		3.0	8.0		

Technical Requirements:

1. Material: PA66, UL-94 V0/2

2. The unmarked tolerance is GB/T1804-H (f)

Order Information

L-KLS8-0217-CSRx-xx x

RoHS
Serise NO.
Mounting Holes
Length
Color: W-White B-Black

ANGLE TOLERANCE		PROJECTION		Description:	
±3°				Snap Rivets	
GENERAL TOLERANCE		UNITS	mm	KLS P/N:	L-KLS8-0217-CSRx-xxx
x.x	±0.30	SHEET SIZE	A4		
x.xx	±0.20	Draw:	Song	2025-10-15	
x.xxx	±0.10	Check:	Daniel	2025-10-15	

NingBo KLS ELECTRONIC CO.,LTD.