Product Specification

Number: L-KLS3-SMT-13*10A

Name: SMD magnetic buzzers Active

Customer:

Date: 2026-10-12

Process Change：V2.0 （Other Change）

KLS electronic

WWW.KLSELE.COM

NINGBO KLS ELECTRONIC CO; LTD

Tel : 0086-574-86828566

Fax : 0086-574-86824882

ADD : NO. 8-1, RONGXIA RD. XIAPU SHANQIAN INDUSTRIAL ZONE BEILUN NINGBO ZHEJIANG.

Compile	Check	Review	Approval
Jenny	Jack.C		

Revision Status

Version	Date	Revision Description	Prepared	Checked	Approved
V1.0	2024-07-26	First issue	Jenny	Daniel	Kandy
V2.0	2026-10-12	Other Change	Jenny	Daniel	Kandy


A. SCOPE

This specification applies magnetic buzzer, **L-KLS3-SMT-13*10A**

B. SPECIFICATION

No.	Item	Unit	Specification	Condition
1	Oscillation Frequency	KHz	2.4 ± 0.3	
2	Operating Voltage	VDC	4 ~ 7	
3	Rated Voltage	VDC	5	
4	Current Consumption	mA	MAX. 30	at Rated Voltage
5	Sound Pressure Level	dB	MIN. 90	at 10cm at Rated Voltage
6	Tone/Pulse Rate		Single	
7	Operating Temperature	℃	-30 ~ +70	
8	Storage Temperature	℃	-40 ~ +85	
9	Dimension	mm	12.8 x 12.8 x H10	See appearance drawing
10	Weight (MAX)	gram	2.5	
11	Housing Material		PPS(Gray)	
12	Leading Pin		Tin Plated Brass(Sn)	See appearance drawing
13	Environmental Protection Regulation		RoHS	High-Temperature Lead Exemption

C. APPEARANCE DRAWING



Tol : ± 0.3 **Unit: mm**


D.TESTING METHOD

Standard Measurement conditions


Temperature:25±2℃ Humidity:45-65%

Acoustic Characteristics:


The oscillation frequency, current consumption and sound pressure are measured by the measuring instruments shown below




In the measuring test, buzzer is placed as follows:



E. VOLTAGE / CURRENT / SOUND PRESSURE CHARACTERISTICS






F. Soldering Condition

(1)Recommendable reflow soldering condition is as follows

(Reflow soldering is twice)

Note:It is requested that reflow soldering should be executed after heat of product goes down to normal.




Heat resistant line

(Used when heat resistant reliability test is performed)

(2)Manual soldering

Manual soldering temperature 350 ℃ within 5 sec.


G. RELIABILITY TEST

NO.	ITEM	TEST CONDITION AND REQUIREMENT
1	High Temperature Test (Storage)	After being placed in a chamber with 85⇨2ºC for 96 hours and then being placed in normal condition for 2 hours. Allowable variation of SPL after test: ⇨10dB.
2	Low Temperature Test (Storage)	After being Placed in a chamber with -40⇨2ºC for 96 hours and then being placed in normal condition for 2 hours. Allowable variation of SPL after test: ⇨10dB.
3	Humidity Test	After being Placed in a chamber with 90-95% R.H. at 40⇨2ºC for 96 hours and then being placed in normal condition for 2 hours. Allowable variation of SPL after test: ⇨10dB.
4	Temperature Cycle Test	The part shall be subjected to 5 cycles. One cycle shall be consist of：  Allowable variation of SPL after test: ⇨10dB.
5	Drop Test	Drop on a hard wood board of 4cm thick, any directions ,6 times, at the height of 75cm . Allowable variation of SPL after test: ⇨10dB.
6	Vibration Test	After being applied vibration of amplitude of 1.5mm with 10 to 55 Hz band of vibration frequency to each of 3 perpendicular directions for 2 hours . Allowable variation of SPL after test: ⇨10dB.
7	Solderability Test	Lead terminals are immersed in rosin for 5 seconds and then immersed in solder bath of +300⇨5ºC for 3⇨1 seconds . 90% min. lead terminals shall be wet with solder (Except the edge of terminals).
8	Terminal Strength Pulling Test	The force of 9.8N(1.0kg) is applied to each terminal in axial direction for 10 seconds. No visible damage and cutting off.


TEST CONDITION.


Standard Test Condition	:	a) Temperature : +5 ~ +35℃	b) Humidity : 45-85%	c) Pressure : 860-1060mbar
一般测试条件	:	a) 温度 : +5 ~ +35℃	b) 湿度 : 45-85%	c) 气压 : 860-1060mbar
Judgment Test Condition	:	a) Temperature : +25 ± 2℃	b) Humidity : 60-70%	c) Pressure : 860-1060mbar
争议时测试条件	:	a) 温度 : +25 ± 2℃	b) 湿度 : 60-70%	c) 气压 : 860-1060mbar

H. PACKING STANDARD



1 Reel : 320PCS





Inner Box	340mmx340mmx40mm	1x320PCS=320PCS